

GPS Antenna Specifications



A20

GPS, SBAS and L-Band (OmniSTAR®)



A30

GPS, SBAS, L-Band (OmniSTAR®) and Beacon

GPS Sensor Specifications

GPS Frequency Range	1.575 GHz (L1)
GPS Bandwidth	20 MHz
GPS LNA Gain	34 dB
GPS LNA Noise	1.4 dB typical

1.575 GHz (L1)
20 MHz
34 dB
1.4 dB typical

Beacon Sensor Specifications

Beacon Frequency Range	N/A
Beacon LNA Gain	N/A

283.5 - 325 KHz
34 dB

L-band Sensor Specifications

L-band Frequency Range	1.525 - 1.585 GHz
L-band LNA Gain	34 dB

1.525 - 1.585 GHz
34 dB

Power Input Specifications

Input Voltage	5 - 12 VDC
Input Current	20-30 mA

5 - 12 VDC
50-60 mA

Mechanical Specifications

Enclosure	AES
Dimensions	55 mm H x 130 mm D (2.2 H x 5.1 D inches)
Weight	363 g (0.8 lb.)
Mounting Options	Magnetic or Fixed Mount - low or high profile (5/8 inch or no. 8-32 screws)

AES
69 mm H x 130 mm D (2.7 H x 5.1 D inches)
590 g (1.31 lb.)
Magnetic or Fixed Mount - low or high profile (5/8 inch or no. 8-32 screws)

Environmental Specifications

Storage Temperature	-40° C to +85° C
Operating Temperature	-30° C to +70° C
Humidity	100% Condensing

-40° C to +85° C
-30° C to +70° C
100% Condensing